

Specification	IEC 60034-1
Manufacturer	AmTecs
Motor type	AMAS-R 63 K4
Rated power	0.12 kW S1 Duty
Speed	1400 rpm
Voltage	220V
Frequency	50 Hz
Connection	Single Phase
Full load current	11 /

Full load current

No-load current

IP55 Enclosure

Insulation class F (temp. rise B)

Max. ambient temp 40 °C

Max. altitude 1000 mtr above sea level

Comment

Cable entry M₂₀ x 1.5 Construction **Aluminium** Weight

Type number Warranty

Kg

Efficiency class	IE1
Load data	100%
Efficiency	55 %
Power factor	0.92
Sound pressure level (1m)	65 dB(A)

Resistance R20 (open) Resistance R20 (Delta)

Full load torque 0.87 Nm

Starting / Full load torque 0.4

Pull up / Full load torque

Pull out / Full load torque 1.7

Starting / Full load current (DOL) Starting / Full load current (Y/D)

Rotor Inertia

Bearing DE 6201 6201 Bearing NDE

AmTecs Ltd	
Charnham Park, Hungerford	
Berkshire, RG17 0YT	
Tel: +44 (0) 1488 686970	sales@amtecs.co.uk
Fax: +44 (0) 1488 686968	www.amtecs.co.uk